



ROUNDS

Hot Rolled (20') Cold Drawn (12' R/L) Alloy: 4150 ANN, 8620 C-1117, C-1215, C-12L14 Alloy (20' R/L) HR: A-36, 1045, 1141 CD: C-1018, C-1045 TG&P, Stress Proof

Size	#/Ft	Size	#/Ft	Size	#/Ft
1/8	0.042	2	10.680	5	66.760
3/16	0.094	2-1/16	11.360	5-1/4	73.600
7/32	0.128	2-1/8	12.060	5-1/2	80.780
1/4	0.167	2-3/16	12.780		
9/32	0.211	2-1/4	13.520	6	96.130
5/16	0.261	2-5/16	14.280	6-1/2	112.800
11/32	0.316	2-3/8	15.060		
3/8	0.376	2-7/16	15.870	7	130.900
7/16	0.511	2-1/2	16.690	7-1/2	150.200
1/2	0.688	2-9/16	17.530		
17/32	0.754	2-5/8	18.400	8	170.900
9/16	0.845	2-11/16	19.290	8-1/2	192.900
19/32	0.941	2-3/4	20.190		
5/8	1.043	2-13/16	21.120	9	216.300
11/16	1.260	2-7/8	22.070	9-1/2	241.000
3/4	1.502	2-15/16	23.040		
25/32	1.630			10	267.000
13/16	1.760	3	24.030		
7/8	2.044	3-1/8	26.080		
15/16	2.350	3-3/16	27.130		
		3-1/4	28.210		
1	2.670	3-3/8	30.420		
1-1/16	3.020	3-7/16	31.550		
1-1/8	3.380	3-1/2	32.710		
1-3/16	3.770	3-5/8	35.090		
1-1/4	4.173	3-11/16	36.310		
1-5/16	4.600	3-3/4	37.550		
1-3/8	5.050	3-7/8	40.100		
1-7/16	5.520	3-15/16	41.400		
1-1/2	6.010				
1-9/16	6.520	4	42.730		
1-5/8	7.051	4-1/4	48.230		
1-11/16	7.600	4-1/2	54.080		
1-3/4	8.180	4-3/4	60.250		
1-13/16	8.770				
1-7/8	9.390				
1-15/16	10.020				

DON'T SEE IT ON THE LIST? CONTACT US!

6079 U.S. 50 West, Hillsboro, Ohio 45133
 (937) 402-7995 • Fax: (937) 393-15190 • dancefarmsupply@gmail.com